

# Calibration Certificate



Cal Cert ID: 149153

Cust. Name: WASHINGTON STATE PATROL

Page 1 of 2

Address: 811 EAST ROANOKE

City: SEATTLE

State/Zip: WA 98102

US

Instr SN: 410004SZ/651315

Out1 Min Range:

8.0000 PSI

Cal Date: 04/10/2018

Instr Descr: CPG 2400

Out1 Max Range:

17.0000 PSI

Cal Time: 12:39 pm

Sensor SN: 410004SZ/651315

Limit of Error:

0.000 %F.S.+ 0.030 % R

Cal Tech: CRISK

Procedure ID: WI02063

Pressure Type:

Absolute

Order Nbr: 22495

#### Test Points Values and Readings

Test Point	Reference Value	Measured Values	Error	Uncertainty
 #	PSI	PSI	% R	PSI
1 2 3 4 5 6 7 8 9 10 11	8.00211 9.80193 11.60174 13.40157 15.20140 17.00131 15.20138 13.40150 11.60166 9.80187 8.00203	8.0023 9.8020 11.6024 13.4022 15.2022 17.0021 15.2024 13.4020 11.6020 9.8021 8.0020	0.002 0.001 0.006 0.005 0.005 0.005 0.007 0.004 0.003 0.002	.00018 .00022 .00026 .00029 .00033 .00037 .00033 .00029 .00026

### Measurement Standards Used in Calibration

Std Type	Serial Number	Description	Assoc. Test Reports	Recal Date
CPD 8000	10017/10016/9994	DH CPD 8000	CAL ID: 119787	12/10/2018

The combined and expanded uncertainty is reported at K=2 providing an approximate 95% confidence level.

#### Remarks and Notes

As Found Calibration. As Left Calibration.

Recalibration Date: 04/10/2019

Prior to "AS FOUND" calibration, zero was adjusted +.0072 PSI.

An asterisk (\*) denotes a measured condition where the error exceeds the maximum permissible error. Dash numbers preceded by the sensor SN reference a primary (-1) or turndown (-2) range as applicable.

The standards and calibration program at Mensor complies with the requirements of ISO/IEC 17025:2005, ANSI/NCSL Z540-1 and Mensor Quality Manual 2.0, Revision R, dated March 10, 2015.

Standards used in this calibration are traceable to SI units of measurements through N.I.S.T. or recognized national metrology institutes. All calibrations are performed in ambient conditions of 23 +/- 4 deg C and 20-80% relative humidity. This calibration certificate shall not be reproduced, except in full, without the written approval of Mensor.



Cal Cert ID:	149153	Page 2 of 2	
I, Christina Kloese	, certify the accuracy of this Calibration Certificate:	Christina Kloesel	
		Calibration Lab Technician	

## Mensor Calibration Certificates and Stickers

Mensor calibration certificates and stickers do not contain calibration intervals unless specified by the customer, as Mensor will not dictate to our customers when they should re-calibrate their instruments.

The Calibration Sticker that is with this product is for your records. Due to the various location requirements of our customers, we do not affix the Calibration Sticker to the product.

For Mensor products, refer to the Calibration Section of your operation manual for the recommended calibration interval.